



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options. Primary finish is outer aluminum trim panels. Secondary finish is inner housing and accent hardware.
- **HOUSING:** Heavy gauge spun solid aluminum drum, hardware, and solid aluminum trim panels can be ordered with complementary finishes. The solid aluminum reflector lamp plate is coated with a reflective white enamel finish.
- **MOUNTING:** Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
CC-390 8"H x 18" Dia.

**2 Finish**

<b>Primary Finish</b>	<b>Secondary Finish</b>
Brushed Solid Aluminum (BA)	Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)	Standard Painted Finishes (PT)

**3 Lamping**  
All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### CC-390

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

### Non-LED Lamps

3N60: (3) 60 watt incandescent

**4 LED Color Temp**

27: 2700K

30: 3000K

35: 3500K

40: 4000K

**5 LED Dimming**

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

**6 Voltage Options**

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

WH: Opal White Acrylic

CD: Ambia configured diffuser (specify option)

1	2	2	3	4	5	6	7
Fixture #	Primary Finish (Finish)	Secondary Fini (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser