







Fixture Number

DP-93-24 9.5"H x 24" Dia. 36" Oah. 11.25"H x 30" Dia. 37" Oah. DP-93-30

DP-93-36 13"H x 36" Dia. 39" Oah.

Finish

Standard Painted Finishes (PT)

Faux Antique Brass (FAB)

Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DP-93-24

LED Options	Lumens	Wattage
B64 Uplight + Downlight	2545 up/1855 down (delivered)	64

Non-LED Lamps

3N100: (3) 100 watt incandescent

DP-93-30

LED Options	Lumens	Wattage
B95R Uplight + Downlight	5090 up/1855 down (delivered)	95

Non-LED Lamps

6N60: (6) 60 watt incandescent

DP-93-36

LED Options	Lumens	Wattage
B145R Uplight + Downlight	8309 up/2782 down (delivered)	145

Non-LED Lamps

6N100: (6) 100 watt incandescent

LED Color Temp

27: 2700K

LED Dimming D0: 0-10v

30: 3000K 35: 3500K

D1: Triac (Leading Edge)* D2: ELV (Trailing Edge)

40: 4000K

Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

Diffuser Options

WH: Opal White Acrylic FX: Faux Alabaster Acrylic

Stem Options

Single Stem (SIN)

Traditional Chain (TCH)



(QAD)

Fixture # Lamping Color Temp Dimming Voltage Diffuser Stem (Finish)