



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **OAH** is standard unless specified.
- **HOUSING:** Extruded aluminum corner bars with heavy gauge aluminum top and bottom panels and machined aluminum 1/4" x 1/2" bar details.
- **MOUNTING:** Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.  
LP-559: Fixture requires structural support such as 2x4 blocking or 3/8" IP stud extending below finished ceiling.
- **CIRCUITS:** Dual-level circuiting for interior lamps and downlight (if specified) standard.
- ETL listed to UL standards for dry and damp locations.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

- LP-555** 10.25"W x 50.25"H x 10.25"L 76" Oah.  
**LP-557** 10.25"W x 62.25"H x 10.25"L 88" Oah.  
**LP-559** 10.25"W x 109.25"H x 10.25"L 135" Oah.

### 2 Finish

- Housing, Stem & Canopy**  
 Standard Painted Finishes (PT)

### 3 Lamping

- LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LP-555

- LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P57 Body Only (57w)	6042 (delivered)	57
P80 Body (57w) + Downlight (23w)	8210 (delivered)	80

#### LP-557

- LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P115 Body Only (115w)	12088 (delivered)	115
P138 Body (115w) + Downlight (23w)	14256 (delivered)	138

#### LP-559

- LED downlight is COB array with 2,168 delivered lumens @ 3500K.

LED Options	Lumens	Wattage
P230 Body Only (230w)	24177 (delivered)	230
P253 Body (230w) + Downlight (23w)	26345 (delivered)	253

### 4 LED Color Temp

- 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

### 5 LED Dimming

- D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

- B50: 50-deg. beam reflector

### 7 Voltage Options

- 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

- WH: Opal White Acrylic

1	2	3	4	5	6	7	8
Fixture #	Housing, Stem (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser