



## 1 Fixture Number

<b>W-101</b>	6"W x 9"H x 2.5" Dia.
<b>W-103</b>	6"W x 8.5"H x 2.5" Dia.
<b>W-105</b>	6"W x 8.5"H x 2.5" Dia.
<b>W-107</b>	6"W x 8.5"H x 2.5" Dia.

## 2 Finish

### Housing

Standard Painted Finishes (PT)

## 3 Lamping

Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### W-101

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

### W-103

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

### W-105

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

### W-107

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

## 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

## 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

## 6 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

## 7 Diffuser Options

AWH: Horizontal Rib Textured Metal  
ALG: Satin Ice Light Green  
ACR: Cherry Red  
ASB: Sky Blue  
APN: Pine  
AMD: Mandarin  
FMC: Mica

1

Fixture #

2

Housing  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser