



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint in black or white colors.
- MOUNTING: Fixture supplied with canopy and hanger for mounting to standard octagon junction box.
- All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
SC-065 7.25"W x 11"H x 7.25" Dia.

2 Finish
White painted finish (WHITE)
Black painted finish (BLACK)

3 Lamping
Includes integral 120-277v 1-100% dimming drivers compatible with 0-10v (120v/277v), Triac and ELV controls (120v only). All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

SC-065

LED Options	Lumens	Wattage
C80 (1) 80-watt LED array	9800 (delivered)	80

4 LED Color Temp
27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Downlight Optics Options
B12: 12-deg. beam reflector
B33: 33-deg. beam reflector
B60: 60-deg. beam reflector

7 Voltage Options
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage