



## Notes

- DIMMING: For a current list of recommended LED dimmers for line-voltage (Triac or ELV) systems see: <https://www.manningltg.com/led-dimming.html>
- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid top and bottom aluminum plates, aluminum corner posts, laser-cut aluminum panels.
- MOUNTING: Fixture supplied with painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations.
- DIMMING: \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

<b>LP-700</b>	22"H x 12" Dia. 48" Oah.
<b>LP-702</b>	30"H x 13.25" Dia. 68" Oah.
<b>LP-704</b>	36"H x 16.25" Dia. 86" Oah.

### 2 Finish

#### Housing

Standard Painted Finishes (PT)

### 3 Lamping

Includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LED Options

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

#### Non-LED Lamps

1N200: 200 watt A-21 med. base

#### LP-702

LED Options	Lumens	Wattage
P40 Body only w/bottom lens (40w)	3796 (delivered)	40
P88 Body (40w) + Downlight (48w)	8128 (delivered)	88
U18 Optional Uplight (18w)	1613 (delivered)	18

#### Non-LED Lamps

8N100 / 1R300: (8) 100 watt incandescent & (1) 300 watt R40 med. base

#### LP-704

LED Options	Lumens	Wattage
P54 Body only w/bottom lens (54w)	5555 (delivered)	54
P109 Body (54w) + Downlight (55w)	11760 (delivered)	109
P150 Body (54w) + Downlight (96w)	14818 (delivered)	150
U44 Optional Uplight (44w)	4038 (delivered)	44

#### Non-LED Lamps

10N100 / 1R500: (10) 100 watt incandescent & (1) 500 watt R40 med. base

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

B60: 60-deg. beam reflector  
B90: 90-deg. beam reflector  
CON: Concentric Ring Louver (approx. 50-deg. beam)


### 7 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

WH: Opal White Acrylic  
IV: Ivory acrylic

### 9 Panel Options



V1

V2

V3

1

Fixture #

2

Housing  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Downlight Opti

7

Voltage

8

Diffuser

9

Panel