



Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Machined aluminum .25-inch wall housing with integral downlight bezel, LED heat sink, and downlight optics.
- MOUNTING: Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- ETL listed to UL standards for dry and damp locations.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
LP-690 12"H x 4.5" Dia. 36" Oah.

2 Finish
 Standard Painted Finishes (PT)

3 Lamping
 Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-690

LED Options	Lumens	Wattage
P10 Downlight (10w)	1208 (initial)	10
P23 Downlight (23w)	2158 (initial)	23

4 LED Color Temp
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options
 B20: 20-deg. beam reflector
 B35: 35-deg. beam reflector
 B50: 50-deg. beam reflector

7 Voltage Options
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Stem Options



Single Stem (SIN)

Aircraft cable with cord (KBL)

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Stem