




1 Fixture Number

DS-610 7.25"W x 16.25"H x 4" Ext.

DS-612 9.25"W x 20.25"H x 5" Ext.

DS-614 9.25"W x 28.25"H x 5" Ext.

2 Finish

End Caps & Frame

Brushed Solid Aluminum (BA)

Polished Brass (PB)

Standard Painted Finishes (PT)

Trim Bars

Brushed Solid Aluminum (BA)

Polished Brass (PB)

Standard Painted Finishes (PT)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-610

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

DS-612

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

2N60: (2) 60 watt incandescent

DS-614

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

5 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)*

D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic

FX: Faux Alabaster Acrylic

8 Fixture Options

BL: Bottom Lens (included with LED options)

TL: Top Lens (included with LED options)

1

Fixture #

2

End Caps & Fra
(Finish)

2

Trim Bars
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser

8

Fixture Option