



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: A thermoformed machined opal white rear housing is standard with a solid aluminum white enameled mounting plate.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
LB-277 8"W x 25.75"H x 4" Ext.
LB-279 6"W x 14"H x 4" Ext.

- 2 Lamping**
 LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-277

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps
 2NT60: (2) 60 watt T-10 incandescent

LB-279

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps
 1NT60: (1) 60 watt T-10 incandescent

- 3 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K
- 4 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 5 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 6 Diffuser Options**
 WH: White Acrylic
 CD: Ambia configured diffuser (specify option)

