



1 Fixture Number

CPI-346-13 15.75"H x 13.5" Dia. 54" Oah.

CPI-346-16 19.75"H x 16.5" Dia. 57" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

CPI-346-13

LED Options	Lumens	Wattage
P26 (1) 26-watt LED array	2835 (initial)	26
P38 (1) 38-watt LED array	4092 (initial)	38

Non-LED Lamps

3N60: (3) 60 watt incandescent

CPI-346-16

LED Options	Lumens	Wattage
P26 (1) 26-watt LED array	2835 (initial)	26
P38 (1) 38-watt LED array	4092 (initial)	38

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

5 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)*

D2: ELV (Trailing Edge)

6 Downlight Optics Options

CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

WH: White Acrylic

IV: Ivory acrylic

FX: Faux Alabaster Acrylic

1

Fixture #

2

Finish
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Downlight Opti

7

Voltage

8

Diffuser