



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of spun aluminum or brass ring trimmed with cast aluminum or brass band. Acrylic bell diffuser and painted white canopy.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
DC-851 11"H x 23" Dia.

**2 Finish**  
Brushed Solid Aluminum (BA)  
Standard Painted Finishes (PT)  
Polished Brass (PB)  
Solid Antique Brass (SAB)  
Faux Antique Brass (FAB)

**Cast Band Design**  
Egg & Dart Cast Trim (EGD)  
Greek Key Cast Trim (GRK)  
Rope Cast Trim (ROP)

**3 Lamping**  
All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

**Non-LED Lamps**  
2N60: (2) 60 watt incandescent

**4 LED Color Temp**  
27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

**5 LED Dimming**  
D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

**6 Voltage Options**  
120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**  
WH: Opal White Acrylic  
FX: Faux Alabaster Acrylic

1	2	2	3	4	5	6	7
Fixture #	Finish (Finish)	Cast Band Desi (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser