


1 Fixture Number

CPI-414-38 33"H x 38" Dia. 177" Oah.

CPI-414-38A 33"H x 38" Dia. 177" Oah.

CPI-414-48 40"H x 48" Dia. 184" Oah.

CPI-414-48A 40"H x 48" Dia. 184" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency. Body, uplights, and downlights separately circuited.

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P245 Body + Downlights	22344 (initial)	245

Non-LED Lamps

6R300 / 1R500 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 100 watt incandescent

CPI-414-38A

Includes (7) 28w LED downlight and (3) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P329 Body + Downlights + Uplights	31920 (initial)	329

Non-LED Lamps

6R300 / 1R500 / 3R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (3) 300 watt R40 med. base & (6) 100 watt incandescent

CPI-414-48

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P259 Body + Downlights	31632 (initial)	259

Non-LED Lamps

6R300 / 1R500 / 6R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 100 watt incandescent

CPI-414-48A

Includes (9) 28w LED downlight and (4) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P427 Body + Downlights + Uplights	50784 (initial)	427

Non-LED Lamps

6R300 / 1R500 / 6R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 300 watt R40 med. base & (6) 100 watt incandescent

4 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

5 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)*

D2: ELV (Trailing Edge)

6 Downlight Optics Options

B60: 60-deg. beam reflector

B90: 90-deg. beam reflector

CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

WH: White Acrylic

IV: Ivory acrylic

FX: Faux Alabaster Acrylic

1

Fixture #

2

Finish
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Downlight Opti

7

Voltage

8

Diffuser