


UPDATED 6/17

323 LED

LUMINOUS PENDANT





FEATURES

- Purpose-built for LED.
- Smooth glare-free up & down light.
- See-through ring design delivers both task & ambient light.
- Canopy mounted drivers reduce installation costs.

ECO INFO

ENERGY: Designed exclusively for LEDs using HPF electronic drivers.

METALS: Aluminum with highest available recycled content for lower embodied energy. Aluminum is valuable and recyclable at the end of the product's useful life. For more information see "GENERAL INFO."

FINISHING: Aluminum finishes are sealed with a handapplied bees wax. No paing or lacquer is used in order to avoid pollution associated with the manufacture and application of these substances. Paint finishes are low VOC and oven cured.

MATERIALS

- White acrylic with matte finish.
- Aluminum ring and canopy.

FINISHES

MB Matte Black **SAL** Satin Aluminum **MW** Matte White MBZ Matte Bronze **CCP** Custom Color Painted finish

LAMPING

Constant current LEDs; 32W, 4400 rated lumens or 40W, 5500 rated lumens. LEDs are 3000K & 80+ CRI. Other CCTs available.

DRIVER


Integral electronic drivers are multi-volt 120/277 and are 0-10V dimmable.








323 **LUMINOUS PENDANT**





PHOTOMETRICS

LightLab Report No. LLi-16183-4. 89 Lm/W. Delivered lumens: 3376. For op[tional higher lumens, increase light levels 25%.



OPTIONS

EMERGENCY BATTERY PACK: Remote mounted EBP, specify **REM**.

MOUNTING: Standard J-box or plaster ring. Safety cable provided.

WEIGHT: 8lbs

NOTE: Integral electronic drivers are multi-volt 120/277 and are 0-10V dimmable.

SPEC GUIDE SAMPLE SPECS: 323-20-LED/47-120-SAL-18"0A





