



Highlights:

- Edge-lit acrylic light guide for uniform appearance and efficient distribution.
- LEDs mounted to removable heat sink for replacement.
- Sleek, low-profile housing available in three sizes.
- 5-year warranty.

Product Number	Dia.	H	Std. OAH	Finish	LED	CCT	Driver Location	Options
DP-770	24"	1.375	36"	PT - Painted BA - Brushed Aluminum	P30 - Pendant LED 30-watts	3000K - Warm 4200K - Cool	REM: Remote DKC: Canopy	DM: 0-10v dimming
DP-774	36"	1.875	36"	PT - Painted BA - Brushed Aluminum	P45 - Pendant LED 45-watts	3000K - Warm 4200K - Cool	REM: Remote DKC: Canopy	DM: 0-10v dimming
DP-776	48"	2.250	36"	PT - Painted BA - Brushed Aluminum	P62 - Pendant LED 62-watts	3000K - Warm 4200K - Cool	REM: Remote DKC: Canopy	DM: 0-10v dimming
Your Spec:								

Notes/Modifications:

Specifications

<p>Construction: Spun aluminum housing, aluminum suspension details and ceiling canopy.</p>	<p>LED: LED source is DC 24-volt. 2700K or 4200K CCT. CRI >80, 3 SDCM. Wattage varies per fixture diameter. L70 50,000 hours.</p>	<p>Photometrics: File available at manningltg.com:</p>
<p>Finish: BA: Brushed aluminum finish with protective lacquer clear coat. PT: All surfaces coated with a low-VOC thermo cure polyester powder paint.</p>	<p>Hanger/Suspension: Adjustable aircraft cable and power cord at 36" standard OAH.</p>	<p>Warranty: Manning Lighting 5-year Warranty.</p>
<p>Electrical: Class 2 constant voltage 120v/277v LED driver mounted in ceiling canopy or remote. 0-10v dimming standard. Wattage listed includes driver efficiency.</p>	<p>Ceiling canopy includes 35-degree swivel ball and mounts to standard junction box. OAH is standard, custom lengths available.</p> <p>Rating: UL listing pending. Union made in USA.</p>	