



- 1 Fixture Number**
DP-800 11.75"H x 12.75" Dia. 36" Oah.
DP-802 18"H x 19.5" Dia. 48" Oah.

- 2 Finish**
Housing, Stem & Canopy
 Standard Painted Finishes (PT)

- 3 Lamping**
 LED option includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DP-800

LED Options	Lumens	Wattage
A32 Akron	2676 Initial	32

DP-802

LED Options	Lumens	Wattage
A48 Akron	5514 Initial	48

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WH: White Acrylic

1

Fixture #

2

Housing, Stem
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser