



Notes

- ETL listed to UL standards for dry, damp, or wet locations.
- HOUSING: Formed aluminum housing with cast aluminum backplate. High transmission clear refractive acrylic lens.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- DRIVER: Integral LED driver compatible with 0-10v, Triac, or ELV dimming.
- MOUNTING: Fixture for installation over standard octagonal junction box.

1 Fixture Number
B-719 6"W x 6"H x 6.6" Ext.

2 Finish
Housing
Standard Painted Finishes (PT)

3 Lamping
Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options		Lumens	Wattage
E13 Downlight		1550 (initial)	13

4 LED Color Temp
27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
CRA: Clear refractive acrylic lens

1	2	3	4	5	6	7
Fixture #	Housing (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser