



Notes

- **HOUSING:** Formed aluminum housing with cast aluminum backplate. High transmission clear refractive acrylic lens. Available with single or dual heads.
- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **DRIVER:** Integral LED driver compatible with 0-10v, Triac, or ELV dimming.
- **MOUNTING:** Aluminum post supplied with base plate mounting. Standard height is 96".

1 Fixture Number
B-921 10"W x 10"H 96" Oah.

2 Finish
Housing
Standard Painted Finishes (PT)

3 Lamping
Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

B-921

LED Options	Lumens	Wattage
E32 Downlight	4240 (initial)	32

4 LED Color Temp
27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
CRA: Clear refractive acrylic lens

8 Fixture Options
DH: Dual Head Post Top

1	2	3	4	5	6	7	8
Fixture #	Housing (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option