



Notes

- HOUSING: Fabricated aluminum housing with acrylic diffuser.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- DRIVER: Integral LED driver compatible with 0-10v, Triac, or ELV dimming.
- MOUNTING: Aluminum post supplied with base plate mounting. Standard height is 36".
- ETL listed to UL standards for dry, damp, or wet locations.

- 1 Fixture Number**
B-926 6"W x 30"H 30" Oah.
- 2 Finish**
Housing
Standard Painted Finishes (PT)

- 3 Lamping**
Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

B-926

LED Options	Lumens	Wattage
E13 Downlight	1550 (initial)	13

- 4 LED Color Temp**
27: 2700K
30: 3000K
35: 3500K
40: 4000K
- 5 LED Dimming**
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

- 6 Voltage Options**
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
CRA: Clear refractive acrylic lens

