



## Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid top and bottom aluminum plates, extruded aluminum corner posts, laser-cut symbol option (if specified).
- MOUNTING: Fixture supplied with painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

- LP-093** 9.25"W x 22.25"H x 9.25"L 48" Oah.
- LP-095** 11.25"W x 30.25"H x 11.25"L 68" Oah.
- LP-097** 13.25"W x 36.25"H x 13.25"L 86" Oah.

### 2 Finish

- |                                |                                |
|--------------------------------|--------------------------------|
| <b>Trim</b>                    | <b>Cross Symbol</b>            |
| Brushed Solid Aluminum (BA)    | Brushed Solid Aluminum (BA)    |
| Standard Painted Finishes (PT) | Standard Painted Finishes (PT) |

### 3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LP-093

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

#### Non-LED Lamps

1N200: 200 watt A-21 med. base

#### LP-095

LED Options	Lumens	Wattage
P40 Body only w/bottom lens (40w)	3796 (delivered)	40
P88 Body (40w) + Downlight (48w)	8128 (delivered)	88
U18 Optional Uplight (18w)	1613 (delivered)	18

#### Non-LED Lamps

8N100 / 1R300: (8) 100 watt incandescent & (1) 300 watt R40 med. base

#### LP-097

LED Options	Lumens	Wattage
P54 Body only w/bottom lens (54w)	5555 (delivered)	54
P109 Body (54w) + Downlight (55w)	11760 (delivered)	109
P150 Body (54w) + Downlight (96w)	14818 (delivered)	150
U44 Optional Uplight (44w)	4038 (delivered)	44

#### Non-LED Lamps

10N100 / 1R500: (10) 100 watt incandescent & (1) 500 watt R40 med. base

### 4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

### 5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

- B60: 60-deg. beam reflector
- B90: 90-deg. beam reflector
- ECR: Black Egg Crate Louver (approx. 40-deg. beam)

### 7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

- WH: Opal White Acrylic
- IV: Ivory acrylic
- FX: Faux Alabaster Acrylic

1

2

2

3

4

5

6

7

8

Fixture #

Trim  
(Finish)

Cross Symbol  
(Finish)

Lamping

Color Temp

Dimming

Downlight Opti

Voltage

Diffuser