



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid aluminum top and bottom end caps, extruded aluminum corner posts and aluminum accent panel. Optional aluminum religious symbol.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
LB-096 8"W x 16"H x 4" Ext.

2 Finish
Trim
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

Cross Symbol
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

3 Lamping
 LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-096

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps
 2NT60: (2) 60 watt T-10 incandescent

4 LED Color Temp
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
 WH: Opal White Acrylic
 IV: Ivory acrylic
 FX: Faux Alabaster Acrylic

