



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid machined aluminum bar details, extruded aluminum corner posts and solid cast aluminum end caps.
- MOUNTING: Fixture supplied with gasketed universal mounting plate for installation over standard octagonal junction box.
- UL and C-UL listed for wet locations.
- Fluorescent ballasts rated to - 22-degree F

1 Fixture Number

- DE-721 7.5"W x 19.75"H x 4" Ext.
- DE-723 7.5"W x 25.75"H x 4" Ext.
- DE-725 7.5"W x 37.25"H x 4" Ext.
- DE-727 7.5"W x 49"H x 4" Ext.

2 Finish

- End Caps/Frame** Standard Painted Finishes (PT)
- Bars** Standard Painted Finishes (PT)

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DE-721

LED Options	Lumens	Wattage
E11	818 (initial)	11

Non-LED Lamps

- 2NT40: (2) 40 watt T-10 incandescent
- 1F27: (1) 27 watt compact fluorescent

DE-723

LED Options	Lumens	Wattage
E17	1226 (initial)	17

Non-LED Lamps

- 3NT40: (3) 40 watt T-10 incandescent
- 1F39: (1) 39 watt compact fluorescent

DE-725

LED Options	Lumens	Wattage
E33	2452 (initial)	33

Non-LED Lamps

- 2F39: (2) 39 watt compact fluorescent

DE-727

LED Options	Lumens	Wattage
E45	3272 (initial)	45

Non-LED Lamps

- 2F40: (2) 40 watt compact fluorescent

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- WH: Opal White Acrylic
- FX: Faux Alabaster Acrylic

8 Fixture Options

- FU: Fusing

1

2

2

3

4

5

6

7

8

Fixture #

End Caps/Frame
(Finish)

Bars
(Finish)

Lamping

Color Temp

Dimming

Voltage

Diffuser

Fixture Option