



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of solid machined aluminum bar details, extruded aluminum corner posts and solid cast aluminum end caps.
- **MOUNTING:** Fixture supplied with gasketed universal mounting plate for installation over standard octagonal junction box.
- ETL listed to UL standards for wet locations.
- Fluorescent ballasts rated to - 22-degree F

### 1 Fixture Number

<b>DE-724</b>	7.5"W x 19.75"H x 4" Ext.
<b>DE-726</b>	7.5"W x 25.75"H x 4" Ext.
<b>DE-728</b>	7.5"W x 37.25"H x 4" Ext.
<b>DE-729</b>	7.5"W x 49"H x 4" Ext.

### 2 Finish

End Caps/Frame	Bars
Standard Painted Finishes (PT)	Standard Painted Finishes (PT)

### 3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### DE-724

LED Options	Lumens	Wattage
E11	818 (initial)	11

#### Non-LED Lamps

2NT40: (2) 40 watt T-10 incandescent

#### DE-726

LED Options	Lumens	Wattage
E17	1226 (initial)	17

#### Non-LED Lamps

3NT40: (3) 40 watt T-10 incandescent

#### DE-728

LED Options	Lumens	Wattage
E33	2452 (initial)	33

#### DE-729

LED Options	Lumens	Wattage
E45	3272 (initial)	45

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v

### 6 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

WH: White Acrylic  
FX: Faux Alabaster Acrylic

1

Fixture #

2

End Caps/Frame  
(Finish)

2

Bars  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser