







# **Notes**

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid machined aluminum bar details, extruded aluminum corner posts and solid cast aluminum end caps.
- MOUNTING: Fixture supplied with gasketed universal mounting plate for installation over standard octagonal junction box.
- ETL listed to UL standards for wet locations.
- Fluorescent ballasts rated to 22-degree F

#### **Fixture Number**

DE-721 7.5"W x 19.75"H x 4" Ext. DE-723 7.5"W x 25.75"H x 4" Ext. DE-725 7.5"W x 37.25"H x 4" Ext. 7.5"W x 49"H x 4" Ext. DE-727

## Finish

## **End Caps/Frame**

### **Bars**

Standard Painted Finishes (PT) Standard Painted Finishes (PT)

## Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

## DE-721

LED Options	Lumens	Wattage
E11	818 (initial)	11

## Non-LED Lamps

2NT40: (2) 40 watt T-10 incandescent

#### DE-723

LED Options	Lumens	Wattage
E17	1226 (initial)	17

## Non-LED Lamps

3NT40: (3) 40 watt T-10 incandescent

### DE-725

LED Options	Lumens	Wattage
E33	2452 (initial)	33

### DE-727

١	LED Options	Lumens	Wattage
	E45	3272 (initial)	45

## **LED Color Temp**

27: 2700K

**LED Dimming** D0: 0-10v

30: 3000K

35: 3500K 40: 4000K

## **Voltage Options**

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

## **Diffuser Options**

WH: Opal White Acrylic

FX: Faux Alabaster Acrylic