



**1 Fixture Number**  
**LP-690** 12"H x 4.5" Dia. 36" Oah.

**2 Finish**  
 Standard Painted Finishes (PT)

**3 Lamping**  
 Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.  
**LP-690**

LED Options	Lumens	Wattage
P10 Downlight (10w)	1208 (initial)	10
P23 Downlight (23w)	2158 (initial)	23

**4 LED Color Temp**  
 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

**5 LED Dimming**  
 D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

**6 Downlight Optics Options**  
 B20: 20-deg. beam reflector  
 B35: 35-deg. beam reflector  
 B50: 50-deg. beam reflector

**7 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

**8 Stem Options**



Single Stem  
(SIN)

Aircraft cable with cord  
(KBL)

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Stem