

Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Spun aluminum fitter and opal white glass shade. Rolled aluminum bar and sheet on decorative band.
- MOUNTING: Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- ETL listed to UL standards for dry and damp locations.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- OAH is standard unless specified.

1 Fixture Number

DP-47-12	12"H x 12" Dia. 52" Oah.
DP-47-14	14"H x 14" Dia. 54" Oah.
DP-47-16	16"H x 16" Dia. 56" Oah.
DP-47-18	18"H x 18" Dia. 58" Oah.

2 Finish

Housing, Stem & Canopy
Standard Painted Finishes (PT)

3 Lamping

LED option includes universal 120-277v 1-100% dimming driver in ceiling canopy compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

Non-LED Lamps

1N60: (1) 60 watt incandescent

DP-47-14

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

Non-LED Lamps

1N60: (1) 60 watt incandescent

DP-47-16

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

Non-LED Lamps

1N60: (1) 60 watt incandescent

DP-47-18

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

Non-LED Lamps

1N60: (1) 60 watt incandescent

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)


6 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WHG: Opal White Glass

8 Panel Options



9 Fixture Options

REM: Remote driver box
DKC: Disk ceiling driver canopy

1

Fixture #

2

Housing, Stem
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser

8

Panel

9

Fixture Option