



- 1 Fixture Number**
DP-47-12 12"H x 12" Dia. 52" Oah.
DP-47-14 14"H x 14" Dia. 54" Oah.
DP-47-16 16"H x 16" Dia. 56" Oah.
DP-47-18 18"H x 18" Dia. 58" Oah.

- 2 Finish**
Housing, Stem & Canopy
 Standard Painted Finishes (PT)

- 3 Lamping**
 LED option includes universal 120-277v 1-100% dimming driver in ceiling canopy compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

Non-LED Lamps
 1N60: (1) 60 watt incandescent

DP-47-14

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

Non-LED Lamps
 1N60: (1) 60 watt incandescent

DP-47-16

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

Non-LED Lamps
 1N60: (1) 60 watt incandescent

DP-47-18

LED Options	Lumens	Wattage
P39 Celeste	4000 delivered	39

Non-LED Lamps
 1N60: (1) 60 watt incandescent

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WHG: Opal White Glass

- 8 Panel Options**
-

- 9 Fixture Options**
 REM: Remote driver box
 DKC: Disk ceiling driver canopy

