



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid brass trim bands, finials and decorative straps. Three chains to spreader with single chain to ceiling hanger.
- MOUNTING: Structural support is required for this heavy fixture. Requires 2 x 4 blocking or 1/2" IP stud extending 1/2" below finished ceiling through center of octagonal junction box.
- CIRCUITS: Wired for two, three, or four circuits with separate neutrals.
- OVERALL HEIGHT: Standard OAH includes fixture height plus 6' chain to spreader and 6' main chain to ceiling.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

- CPI-436-40** 20"H x 40" Dia. 164" Oah.
- CPI-436-40A** 20"H x 40" Dia. 164" Oah.
- CPI-436-48** 23"H x 48" Dia. 167" Oah.
- CPI-436-48A** 23"H x 48" Dia. 167" Oah.

### 2 Finish

Standard Painted Finishes (PT)

### 3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency. Body, uplights, ~~CPI-436-40~~ lights separately circuited.

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

| LED Options            | Lumens          | Wattage |
|------------------------|-----------------|---------|
| P245 Body + Downlights | 22344 (initial) | 245     |

#### Non-LED Lamps

6R300 / 1R500 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 100 watt incandescent

#### CPI-436-40A

Includes (7) 28w LED downlight and (3) 28w uplight arrays, each producing 3,192 lumens at 3500K.

| LED Options                       | Lumens          | Wattage |
|-----------------------------------|-----------------|---------|
| P329 Body + Downlights + Uplights | 31920 (initial) | 329     |

#### Non-LED Lamps

6R300 / 1R500 / 3R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (3) 300 watt R40 med. base & (6) 100 watt incandescent

#### CPI-436-48

Includes (9) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

| LED Options            | Lumens          | Wattage |
|------------------------|-----------------|---------|
| P315 Body + Downlights | 38016 (initial) | 315     |

#### Non-LED Lamps

8R300 / 1R500 / 3R300 / 6N100: (8) 300 watt R40 med. base & (1) 500 watt R40 med. base & (8) 100 watt incandescent

#### CPI-436-48A

Includes (9) 28w LED downlight and (4) 28w uplight arrays, each producing 3,192 lumens at 3500K.

| LED Options                       | Lumens          | Wattage |
|-----------------------------------|-----------------|---------|
| P427 Body + Downlights + Uplights | 50784 (initial) | 427     |

#### Non-LED Lamps

8R300 / 1R500 / 4R300 / 8N100: (8) 300 watt R40 med. base & (1) 500 watt R40 med. base & (4) 300 watt R40 med. base & (8) 100 watt incandescent

### 4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

### 5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

CON: Concentric Ring Louver (approx. 50-deg. beam)

### 7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

WH: Opal White Acrylic

| 1         | 2               | 3       | 4          | 5       | 6              | 7       | 8        |
|-----------|-----------------|---------|------------|---------|----------------|---------|----------|
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser |