



LPI-436-40

LPI-436-48

Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of solid brass trim bands, finials and decorative straps. Three chains to spreader with single chain to ceiling hanger.
- **MOUNTING:** Structural support is required for this heavy fixture. Requires 2 x 4 blocking or 1/2" IP stud extending 1/2" below finished ceiling through center of octagonal junction box.
- **CIRCUITS:** Wired for two, three, or four circuits with separate neutrals.
- **OVERALL HEIGHT:** Standard OAH includes fixture height plus 6' chain to spreader and 6' main chain to ceiling.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LPI-436-40** 49"H x 40" Dia. 193" Oah.
LPI-436-40A 49"H x 40" Dia. 193" Oah.
LPI-436-48 64"H x 48" Dia. 208" Oah.
LPI-436-48A 64"H x 48" Dia. 208" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LPI-436-40

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

| LED Options | Lumens | Wattage |
|------------------------|-----------------|---------|
| P285 Body + Downlights | 35760 (initial) | 285 |

Non-LED Lamps

6R300 / 1R500 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (12) 100 watt incandescent

LPI-436-40A

Includes (7) 28w LED downlight and (3) 28w uplight arrays, each producing 3,192 lumens at 3500K.

| LED Options | Lumens | Wattage |
|-----------------------------|-----------------|---------|
| P369 Body+Uplight+Downlight | 38112 (initial) | 369 |

Non-LED Lamps

6R300 / 1R500 / 3R300 / 12N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (3) 300 watt R40 med. base & (12) 100 watt incandescent

LPI-436-48

Includes (9) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

| LED Options | Lumens | Wattage |
|------------------------|-----------------|---------|
| P355 Body + Downlights | 44208 (initial) | 355 |

Non-LED Lamps

8R300 / 1R500 / 3R300 / 12N100: (8) 300 watt R40 med. base & (1) 500 watt R40 med. base & (14) 60 watt incandescent

LPI-436-48A

Includes (9) 28w LED downlight and (4) 28w uplight arrays, each producing 3,192 lumens at 3500K.

| LED Options | Lumens | Wattage |
|-----------------------------|-----------------|---------|
| P467 Body+Uplight+Downlight | 56976 (initial) | 467 |

Non-LED Lamps

8R300 / 1R500 / 4R300 / 14N60: (8) 300 watt R40 med. base & (1) 500 watt R40 med. base & (4) 300 watt R40 med. base & (14) 60 watt incandescent

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
 B90: 90-deg. beam reflector
 CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: White Acrylic

| | | | | | | | |
|-----------|-----------------|---------|------------|---------|----------------|---------|----------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser |