



**1 Fixture Number**  
**CC-226** 6.5"H x 17" Dia.

**2 Finish**  
**Trim**  
 Brushed Solid Aluminum (BA)  
 Polished Brass (PB)  
 Standard Painted Finishes (PT)

**3 Lamping**  
 All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**CC-226**

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

**Non-LED Lamps**  
 3N60: (3) 60 watt incandescent

**4 LED Color Temp**  
 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

**5 LED Dimming**  
 D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

**6 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**  
 WH: White Acrylic

**1**

Fixture #

**2**

Trim  
(Finish)

**3**

Lamping

**4**

Color Temp

**5**

Dimming

**6**

Voltage

**7**

Diffuser