



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of (3) spun aluminum or brass trim rings over a thermoformed white acrylic bowl.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

CC-226 6.5"H x 17" Dia.

2 Finish

Trim

- Brushed Solid Aluminum (BA)
- Polished Brass (PB)
- Standard Painted Finishes (PT)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

CC-226

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- WH: White Acrylic

1	2	3	4	5	6	7
Fixture #	Trim (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser