



Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Four spun aluminum or brass trim rings over an extruded white acrylic cylinder diffuser.
- MOUNTING: Fixture supplied with painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
 - LP-520** 22"H x 9.25" Dia. 48" Oah.
 - LP-522** 30"H x 11.5" Dia. 68" Oah.
 - LP-524** 36"H x 13.75" Dia. 86" Oah.

- 2 Finish**
 - Trim**
 - Brushed Solid Aluminum (BA)
 - Polished Brass (PB)
 - Standard Painted Finishes (PT)

- 3 Lamping**
 - LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-520

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

- Non-LED Lamps**
- 1N200: 200 watt A-21 med. base

LP-522

LED Options	Lumens	Wattage
P40 Body only w/bottom lens (40w)	3796 (delivered)	40
P88 Body (40w) + Downlight (48w)	8128 (delivered)	88
U18 Optional Uplight (18w)	1613 (delivered)	18

- Non-LED Lamps**
- 8N75 / 1R300: (8) 75 watt incandescent & (1) 300 watt R40 med. base

LP-524

LED Options	Lumens	Wattage
P54 Body only w/bottom lens (54w)	5555 (delivered)	54
P109 Body (54w) + Downlight (55w)	11760 (delivered)	109
P150 Body (54w) + Downlight (96w)	14818 (delivered)	150
U44 Optional Uplight (44w)	4038 (delivered)	44

- Non-LED Lamps**
- 10N100 / 1R500: (10) 100 watt incandescent & (1) 500 watt R40 med. base

- 4 LED Color Temp**
 - 27: 2700K
 - 30: 3000K
 - 35: 3500K
 - 40: 4000K
- 5 LED Dimming**
 - D0: 0-10v
 - D1: Triac (Leading Edge)*
 - D2: ELV (Trailing Edge)

- 6 Downlight Optics Options**
 - B60: 60-deg. beam reflector
 - B90: 90-deg. beam reflector
 - CON: Concentric Ring Louver (approx. 50-deg. beam)
 - ECR: Black Egg Crate Louver (approx. 40-deg. beam)

- 7 Voltage Options**
 - 120: 120 volt
 - 277: 277 volt (Not available with incandescent lamp options)

- 8 Diffuser Options**
 - WH: Opal White Acrylic

