



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid machined aluminum or brass bar details and extruded aluminum corner posts. Thermoformed acrylic half cylinder.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

DS-620	7.25"W x 16"H x 4" Ext.
DS-622	9.25"W x 20"H x 5" Ext.
DS-624	9.25"W x 28"H x 5" Ext.

2 Finish

End Caps & Frame

Brushed Solid Aluminum (BA)
Polished Brass (PB)
Standard Painted Finishes (PT)

Trim Bars

Brushed Solid Aluminum (BA)
Polished Brass (PB)
Standard Painted Finishes (PT)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-620

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

DS-622

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

2N60: (2) 60 watt incandescent

DS-624

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic
FX: Faux Alabaster Acrylic

8 Fixture Options

BL: Bottom Lens (included with LED options)
TL: Top Lens (included with LED options)

1

2

2

3

4

5

6

7

8

Fixture #

End Caps & Fra
(Finish)

Trim Bars
(Finish)

Lamping

Color Temp

Dimming

Voltage

Diffuser

Fixture Option