



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid machined aluminum or brass bar details and extruded aluminum corner posts. Thermoformed acrylic half cylinder.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- DS-620** 7.25"W x 16"H x 4" Ext.
- DS-622** 9.25"W x 20"H x 5" Ext.
- DS-624** 9.25"W x 28"H x 5" Ext.

2 Finish

End Caps & Frame

- Brushed Solid Aluminum (BA)
- Polished Brass (PB)
- Standard Painted Finishes (PT)

Trim Bars

- Brushed Solid Aluminum (BA)
- Polished Brass (PB)
- Standard Painted Finishes (PT)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-620

| LED Options | Lumens | Wattage |
|-------------|-----------------|---------|
| S7 | 612 (delivered) | 7 |

Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

DS-622

| LED Options | Lumens | Wattage |
|-------------|-----------------|---------|
| S16 | 995 (delivered) | 16 |

Non-LED Lamps

2N60: (2) 60 watt incandescent

DS-624

| LED Options | Lumens | Wattage |
|-------------|-----------------|---------|
| S16 | 995 (delivered) | 16 |

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- WH: Opal White Acrylic
- FX: Faux Alabaster Acrylic

8 Fixture Options

- BL: Bottom Lens (included with LED options)
- TL: Top Lens (included with LED options)

