



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Solid machined aluminum or brass bar details and extruded aluminum corner posts. Thermoformed acrylic half cylinder.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

<b>DS-620</b>	7.25"W x 16"H x 4" Ext.
<b>DS-622</b>	9.25"W x 20"H x 5" Ext.
<b>DS-624</b>	9.25"W x 28"H x 5" Ext.

### 2 Finish

#### End Caps & Frame

Brushed Solid Aluminum (BA)  
Polished Brass (PB)  
Standard Painted Finishes (PT)

#### Trim Bars

Brushed Solid Aluminum (BA)  
Polished Brass (PB)  
Standard Painted Finishes (PT)

### 3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### DS-620

LED Options	Lumens	Wattage
S7	612 (delivered)	7

#### Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

#### DS-622

LED Options	Lumens	Wattage
S16	995 (delivered)	16

#### Non-LED Lamps

2N60: (2) 60 watt incandescent

#### DS-624

LED Options	Lumens	Wattage
S16	995 (delivered)	16

#### Non-LED Lamps

3N60: (3) 60 watt incandescent

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

### 6 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

WH: Opal White Acrylic  
FX: Faux Alabaster Acrylic

### 8 Fixture Options

BL: Bottom Lens (included with LED options)  
TL: Top Lens (included with LED options)

1

Fixture #

2

End Caps & Fra  
(Finish)

2

Trim Bars  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser

8

Fixture Option