



Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Two spun aluminum or brass trim rings over an extruded white acrylic cylinder diffuser.
- MOUNTING: Fixture supplied with painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LP-530** 22"H x 9.25" Dia. 48" Oah.
LP-532 30"H x 11.5" Dia. 68" Oah.
LP-534 36"H x 13.75" Dia. 86" Oah.

2 Finish

- Trim**
 Brushed Solid Aluminum (BA)
 Polished Brass (PB)
 Standard Painted Finishes (PT)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-530

| LED Options | Lumens | Wattage |
|-----------------------------------|------------------|---------|
| P27 Body only w/bottom lens (27W) | 2730 (delivered) | 27 |
| P63 Body (27w) + Downlight (36w) | 5471 (delivered) | 63 |

Non-LED Lamps

1N200: 200 watt A-21 med. base

LP-532

| LED Options | Lumens | Wattage |
|-----------------------------------|------------------|---------|
| P40 Body only w/bottom lens (40w) | 3796 (delivered) | 40 |
| P88 Body (40w) + Downlight (48w) | 8128 (delivered) | 88 |
| U18 Optional Uplight (18w) | 1613 (delivered) | 18 |

Non-LED Lamps

8N75 / 1R300: (8) 75 watt incandescent & (1) 300 watt R40 med. base

LP-534

| LED Options | Lumens | Wattage |
|-----------------------------------|-------------------|---------|
| P54 Body only w/bottom lens (54w) | 5555 (delivered) | 54 |
| P109 Body (54w) + Downlight (55w) | 11760 (delivered) | 109 |
| P150 Body (54w) + Downlight (96w) | 14818 (delivered) | 150 |
| U44 Optional Uplight (44w) | 4038 (delivered) | 44 |

Non-LED Lamps

10N100 / 1R500: (10) 100 watt incandescent & (1) 500 watt R40 med. base

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
 B90: 90-deg. beam reflector
 CON: Concentric Ring Louver (approx. 50-deg. beam)
 ECR: Black Egg Crate Louver (approx. 40-deg. beam)

7 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: Opal White Acrylic

| | | | | | | | |
|-----------|---------------|---------|------------|---------|----------------|---------|----------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| Fixture # | Trim (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser |