


1 Fixture Number

DS-730 7.25"W x 16"H x 4" Ext.
DS-732 9.25"W x 20"H x 5" Ext.
DS-734 9.25"W x 28"H x 5" Ext.

2 Finish
End Caps & Frame

Brushed Solid Aluminum (BA)
 Polished Brass (PB)
 Standard Painted Finishes (PT)

Trim Bars & Leaf

Brushed Solid Aluminum (BA)
 Polished Brass (PB)
 Standard Painted Finishes (PT)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-730

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

DS-732

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

2N60: (2) 60 watt incandescent

DS-734

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp

27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic
 FX: Faux Alabaster Acrylic

8 Fixture Options

BL: Bottom Lens (included with LED options)
 TL: Top Lens (included with LED options)

1	2	2	3	4	5	6	7	8
Fixture #	End Caps & Fra (Finish)	Trim Bars & Le (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option