



1 Fixture Number

- DS-610** 7.25"W x 16.25"H x 4" Ext.
- DS-612** 9.25"W x 20.25"H x 5" Ext.
- DS-614** 9.25"W x 28.25"H x 5" Ext.

2 Finish

- | | |
|--------------------------------|--------------------------------|
| End Caps & Frame | Trim Bars |
| Brushed Solid Aluminum (BA) | Brushed Solid Aluminum (BA) |
| Polished Brass (PB) | Polished Brass (PB) |
| Standard Painted Finishes (PT) | Standard Painted Finishes (PT) |

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DS-610

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

DS-612

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

2N60: (2) 60 watt incandescent

DS-614

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- WH: White Acrylic
- FX: Faux Alabaster Acrylic

8 Fixture Options

- BL: Bottom Lens (included with LED options)
- TL: Top Lens (included with LED options)

1

2

2

3

4

5

6

7

8

Fixture #

End Caps & Fra
(Finish)

Trim Bars
(Finish)

Lamping

Color Temp

Dimming

Voltage

Diffuser

Fixture Option