



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of extruded aluminum frame with solid aluminum or brass bars over an extruded white acrylic cylinder diffuser.
- **MOUNTING:** Fixture supplied with gasketed universal mounting plate for installation over standard octagonal junction box.
- UL and C-UL listed for wet locations.
- Fluorescent ballasts rated to - 22-degree F

### 1 Fixture Number

<b>DE-620</b>	7.25"W x 16"H x 4" Ext.
<b>DE-622</b>	9.25"W x 20"H x 5" Ext.
<b>DE-624</b>	9.25"W x 28"H x 5" Ext.

### 2 Finish

End Caps/Frame	Bars
Standard Painted Finishes (PT)	Standard Painted Finishes (PT)

### 3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### DE-620

LED Options	Lumens	Wattage
E11	818 (initial)	11

#### Non-LED Lamps

2NT40: (2) 40 watt T-10 incandescent

#### DE-622

LED Options	Lumens	Wattage
E17	1226 (initial)	17

#### Non-LED Lamps

2N60: (2) 60 watt incandescent

#### DE-624

LED Options	Lumens	Wattage
E23	1636 (initial)	23

#### Non-LED Lamps

3N60: (3) 60 watt incandescent

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v

### 6 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

WH: Opal White Acrylic  
FX: Faux Alabaster Acrylic

### 8 Fixture Options

PC: Photo Cell

1	2	2	3	4	5	6	7	8
Fixture #	End Caps/Frame (Finish)	Bars (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option