



1 Fixture Number

- DE-630** 7.25"W x 16"H x 4" Ext.
- DE-632** 9.25"W x 20"H x 5" Ext.
- DE-634** 9.25"W x 28"H x 5" Ext.

2 Finish

- | | |
|--------------------------------|--------------------------------|
| End Caps/Frame | Bars |
| Standard Painted Finishes (PT) | Standard Painted Finishes (PT) |

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DE-630

LED Options	Lumens	Wattage
E11	818 (initial)	11

Non-LED Lamps

2NT40: (2) 40 watt T-10 incandescent

DE-632

LED Options	Lumens	Wattage
E17	1226 (initial)	17

Non-LED Lamps

2N60: (2) 60 watt incandescent

DE-634

LED Options	Lumens	Wattage
E23	1636 (initial)	23

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

D0: 0-10v

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- WH: White Acrylic
- FX: Faux Alabaster Acrylic

8 Fixture Options

- PC: Photo Cell

1

2

2

3

4

5

6

7

8

Fixture #

End Caps/Frame
(Finish)

Bars
(Finish)

Lamping

Color Temp

Dimming

Voltage

Diffuser

Fixture Option