



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of extruded aluminum frame with solid aluminum or brass bars and laser-cut aluminum or brass leaf accents over an extruded white acrylic cylinder diffuser.
- MOUNTING: Fixture supplied with gasketed universal mounting plate for installation over standard octagonal junction box.
- ETL listed to UL standards for wet locations.
- Fluorescent ballasts rated to - 22-degree F

1 Fixture Number

- DE-730 7.25"W x 16"H x 4" Ext.
- DE-732 9.25"W x 20"H x 5" Ext.
- DE-734 9.25"W x 28"H x 5" Ext.

2 Finish

- End Caps/Frame** Standard Painted Finishes (PT)
- Bars** Standard Painted Finishes (PT)

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DE-730

LED Options	Lumens	Wattage
E11	818 (initial)	11

Non-LED Lamps

2NT40: (2) 40 watt T-10 incandescent

DE-732

LED Options	Lumens	Wattage
E17	1226 (initial)	17

Non-LED Lamps

2N60: (2) 60 watt incandescent

DE-734

LED Options	Lumens	Wattage
E23	1636 (initial)	23

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

D0: 0-10v

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- WH: Opal White Acrylic
- FX: Faux Alabaster Acrylic

8 Fixture Options

- PC: Photo Cell

