



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of extruded aluminum frame with solid aluminum or brass bars and laser-cut aluminum or brass leaf accents over an extruded white acrylic cylinder diffuser.
- MOUNTING: Fixture supplied with gasketed universal mounting plate for installation over standard octagonal junction box.
- ETL listed to UL standards for wet locations.
- Fluorescent ballasts rated to - 22-degree F

- Fixture Number**
DE-730 7.25"W x 16"H x 4" Ext.
DE-732 9.25"W x 20"H x 5" Ext.
DE-734 9.25"W x 28"H x 5" Ext.
- Finish**
End Caps/Frame Standard Painted Finishes (PT) **Bars** Standard Painted Finishes (PT)
- Lamping**
 Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.
DE-730

| LED Options | Lumens | Wattage |
|-------------|---------------|---------|
| E11 | 818 (initial) | 11 |

Non-LED Lamps
2NT40: (2) 40 watt T-10 incandescent

DE-732

| LED Options | Lumens | Wattage |
|-------------|----------------|---------|
| E17 | 1226 (initial) | 17 |

Non-LED Lamps
2N60: (2) 60 watt incandescent

DE-734

| LED Options | Lumens | Wattage |
|-------------|----------------|---------|
| E23 | 1636 (initial) | 23 |

Non-LED Lamps
3N60: (3) 60 watt incandescent
- LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K
- LED Dimming**
 D0: 0-10v
- Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)
- Diffuser Options**
 WH: Opal White Acrylic
 FX: Faux Alabaster Acrylic
- Fixture Options**
 PC: Photo Cell

