



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of cast aluminum frame and one-piece impact resistant acrylic diffuser.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for wet locations.
- Fluorescent ballasts rated to - 22-degree F

- 1 Fixture Number**  
**DE-220** 11"W x 13.5"H x 4" Ext.  
**DE-230** 15.5"W x 20"H x 5.4" Ext.

- 2 Finish**  
 Standard Painted Finishes (PT)

- 3 Lamping**  
 Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**DE-220**

| LED Options | Lumens        | Wattage |
|-------------|---------------|---------|
| E7          | 401 (initial) | 7       |

**DE-230**

| LED Options | Lumens        | Wattage |
|-------------|---------------|---------|
| E11         | 818 (initial) | 11      |

- 4 LED Color Temp**  
 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

- 5 LED Dimming**  
 D0: 0-10v

- 6 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**  
 WH: Opal White Acrylic

