

# **Notes**

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer.
   Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of spun aluminum housing clad with stainless steel or aluminum textured metal trim. Opal white acrylic diffuser.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- $\ensuremath{\mathsf{ETL}}$  listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

#### Fixture Number

DP-890 5"H x 23.5" Dia. 31" Oah.
DP-892 5.5"H x 29" Dia. 31" Oah.
DP-894 6.75"H x 34.25" Dia. 32" Oah.

2 Finish

Housing Textured metal accent trim
Standard Painted Finishes (PT) Standard Painted Finishes (PT)

Brushed Solid Aluminum (BA) Stainless Steel (SS)

### 3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### DP-890

LED Options	Lumens	Wattage
B48 Downlight + Uplight (48w)	1402 up/1533 down (delivered)	48
B48R Uplight + Downlight (48w)	2804 up/766 down (delivered)	48

### DP-892

LED Options	Lumens	Wattage
B96 Downlight + Uplight (96w)	2804 up/3066 down (delivered)	96
B96R Uplight + Downlight (96w)	5608 up/1533 down (delivered)	96

### DP-894

LED Options	Lumens	Wattage
B128 Downlight + Uplight (128w)	2804 up/4599 down (delivered)	128
B128R Uplight + Downlight (128w)	8412 up/1533 down (delivered)	128

**LED Dimming** 

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

D0: 0-10v

## 4 LED Color Temp

27: 2700K

30: 3000K 35: 3500K


40: 4000K

6 Voltage Options 120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

WH: White Acrylic







Single Stem (SIN)



Aircraft Cable (CBL)



Satellite Rods (QAD)



1/4" Plate Fins (FIN)