

Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of spun aluminum housing clad with stainless steel or aluminum textured metal trim. Opal white acrylic diffuser.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

Fixture Number

DP-891 5.75"H x 23.5" Dia. 32" Oah. DP-893 8"H x 29" Dia. 34" Oah. DP-895 9.75"H x 34.25" Dia. 36" Oah.

Finish

Housing Textured metal accent trim Standard Painted Finishes (PT) Standard Painted Finishes (PT) Brushed Solid Aluminum (BA) Stainless Steel (SS)

Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DP-891

LED Options	Lumens	Wattage
B48 Downlight + Uplight (48w)	1402 up/1533 down (delivered)	48
B48R Uplight + Downlight (48w)	2804 up/766 down (delivered)	48

DP-893

LED Options	Lumens	Wattage
B96 Downlight + Uplight (96w)	2804 up/3066 down (delivered)	96
B96R Uplight + Downlight (96w)	5608 up/1533 down (delivered)	96

DP-895

LED Options	Lumens	Wattage
B128 Downlight + Uplight (128w)	2804 up/4599 down (delivered)	128
B128R Uplight + Downlight (128w)	8412 up/1533 down (delivered)	128

LED Dimming

D1: Triac (Leading Edge)*

D2: ELV (Trailing Edge)

D0: 0-10v

LED Color Temp

27: 2700K

30: 3000K 35: 3500K

40: 4000K


Voltage Options

120: 120 volt


277: 277 volt (Not available with incandescent lamp options)

Diffuser Options

WH: White Acrylic











1/4" Plate Fins

(FIN)