



Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Heavy gauge spun solid aluminum drum, hardware, and solid aluminum trim panels can be ordered with complementary finishes. Solid aluminum lamp plate reflector is coated with a reflective white enamel finish.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
LP-390 8"H x 18" Dia. 34" Oah.
LP-392 9"H x 24" Dia. 35" Oah.

- 2 Finish**
- | | |
|--------------------------------|--------------------------------|
| Primary Finish | Secondary Finish |
| Brushed Solid Aluminum (BA) | Brushed Solid Aluminum (BA) |
| Standard Painted Finishes (PT) | Standard Painted Finishes (PT) |

- 3 Lamping**
 LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-390

| LED Options | Lumens | Wattage |
|-------------------------|-------------------------------|---------|
| B32 Uplight + Downlight | 1097 up/1097 down (delivered) | 32 |

Non-LED Lamps
 3N60: (3) 60 watt incandescent

LP-392

| LED Options | Lumens | Wattage |
|-------------------------------|-------------------------------|---------|
| B48 Downlight + Uplight (48w) | 1402 up/1533 down (delivered) | 48 |

Non-LED Lamps
 3N60: (3) 60 watt incandescent

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K
- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WH: Opal White Acrylic
 CD: Ambia configured diffuser (specify option)

- 8 Stem Options**
- | | | | |
|-------------------|----------------------|----------------------|-----------------------|
| | | | |
| Single Stem (SIN) | Aircraft Cable (CBL) | Satellite Rods (QAD) | 1/4" Plate Fins (FIN) |

| | | | | | | | | |
|-----------|-------------------------|-------------------------|---------|------------|---------|---------|----------|------|
| 1 | 2 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| Fixture # | Primary Finish (Finish) | Secondary Fini (Finish) | Lamping | Color Temp | Dimming | Voltage | Diffuser | Stem |