





Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Heavy gauge spun solid aluminum drum, hardware, and solid aluminum trim panels can be ordered with complementary finishes. Solid aluminum lamp plate reflector is coated with a reflective white enamel finish.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

LP-390 8"H x 18" Dia. 34" Oah.
LP-392 9"H x 24" Dia. 35" Oah.

2 Finish

Primary Finish
Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)

Secondary Finish
Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-390

LED Options	Lumens	Wattage
B32 Uplight + Downlight	1097 up/1097 down (delivered)	32

Non-LED Lamps
3N60: (3) 60 watt incandescent

LP-392

LED Options	Lumens	Wattage
B48 Downlight + Uplight (48w)	1402 up/1533 down (delivered)	48

Non-LED Lamps
3N60: (3) 60 watt incandescent

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic
CD: Ambia configured diffuser (specify option)

8 Stem Options


Single Stem (SIN)


Aircraft Cable (CBL)


Satellite Rods (QAD)


1/4" Plate Fins (FIN)

1 Fixture # | 2 Primary Finish (Finish) | 2 Secondary Fini (Finish) | 3 Lamping | 4 Color Temp | 5 Dimming | 6 Voltage | 7 Diffuser | 8 Stem

©2018 Manning Lighting Inc. Sheboygan, WI 53083 Phone: 920-458-2184 Web: manningltg.com Email: info@manningltg.com Design modification rights reserved. Made in USA.