



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Heavy gauge solid aluminum housing and backplate can be ordered with complementary finishes. Independent lamping/mounting chassis in white enamel finish.
- **MOUNTING:** Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

LB-390 8"W x 16"H x 4" Ext.
LB-392 8"W x 24"H x 4" Ext.

2 Finish

Primary Finish

Standard Painted Finishes (PT)

Secondary Finish

Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-390

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps

2NT40: (2) 40 watt T-10 incandescent

LB-392

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

3NT40: (3) 40 watt T-10 incandescent

4 LED Color Temp

27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic
 CD: Ambia configured diffuser (specify option)

1	2	2	3	4	5	6	7
Fixture #	Primary Finish (Finish)	Secondary Fini (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser