



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Heavy gauge solid aluminum housing and backplate can be ordered with complementary finishes. Independent lamping/mounting chassis in white enamel finish.
- MOUNTING: Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**
LB-390 8"W x 16"H x 4" Ext.
LB-392 8"W x 24"H x 4" Ext.

- 2 Finish**
- | | |
|--------------------------------|---|
| Primary Finish | Secondary Finish |
| Standard Painted Finishes (PT) | Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT) |

- 3 Lamping**
 LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-390

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps
 2NT40: (2) 40 watt T-10 incandescent

LB-392

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps
 3NT40: (3) 40 watt T-10 incandescent

- | | | |
|-------------------------|-----------|----------------------|
| 4 LED Color Temp | 27: 2700K | 5 LED Dimming |
| | 30: 3000K | |
| | 35: 3500K | |
| | 40: 4000K | |

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WH: Opal White Acrylic
 CD: Ambia configured diffuser (specify option)

1	2	2	3	4	5	6	7
Fixture #	Primary Finish (Finish)	Secondary Fini (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser