



## Notes

- OAH is standard unless specified. Standard OAH includes fixture height plus 3' chain to spreader and 6' main chain to ceiling.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid cast aluminum trim panels with fabricated steel corner trim posts.
- MOUNTING: Structural support is required for this heavy fixture. Requires 2 x 4 blocking or 1/2" IP stud extending 1/2" below finished ceiling through center of octagonal junction box.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

**LPI-303-24** 53"H x 24" Dia. 161" Oah.  
**LPI-303-30** 70"H x 30" Dia. 178" Oah.

### 2 Finish

Standard Painted Finishes (PT)

### 3 Lamping

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LPI-303-24

| LED Options                       | Lumens            | Wattage |
|-----------------------------------|-------------------|---------|
| P109 Body (54w) + Downlight (55w) | 11760 (delivered) | 109     |
| P150 Body (54w) + Downlight (96w) | 14818 (delivered) | 150     |
| U44 Optional Uplight (44w)        | 4038 (delivered)  | 44      |

#### Non-LED Lamps

6N60 / 3R300 / 1R500: (6) 60 watt incandescent & (3) 300 watt R40 med. base & (1) 500 watt R40 med. base

#### LPI-303-30

| LED Options                       | Lumens           | Wattage |
|-----------------------------------|------------------|---------|
| P177 Body (81w) + Downlight (96w) | 22321 (initial)  | 177     |
| U44 Optional Uplight (44w)        | 4038 (delivered) | 44      |

#### Non-LED Lamps

9N60 / 3R300 / 1R500: (9) 60 watt incandescent & (3) 300 watt R40 med. base & (1) 500 watt R40 med. base

### 4 LED Color Temp

27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

### 5 LED Dimming

D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

B60: 60-deg. beam reflector  
 B90: 90-deg. beam reflector  
 CON: Concentric Ring Louver (approx. 50-deg. beam)

### 7 Voltage Options

120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

WH: Opal White Acrylic  
 IV: Ivory acrylic  
 FX: Faux Alabaster Acrylic

1

Fixture #

2

Finish  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Downlight Opti

7

Voltage

8

Diffuser