



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Formed steel material with cast aluminum rope trim detail.
- **MOUNTING:** Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

**DC-93-16** 8"H x 16" Dia.  
**DC-93-18** 9"H x 18" Dia.  
**DC-93-22** 11"H x 22" Dia.

### 2 Finish

Standard Painted Finishes (PT)  
 Faux Antique Brass (FAB)

### 3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### DC-93-16

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

#### Non-LED Lamps

2N60: (2) 60 watt incandescent

#### DC-93-18

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

#### Non-LED Lamps

3N60: (3) 60 watt incandescent

#### DC-93-22

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

#### Non-LED Lamps

3N60: (3) 60 watt incandescent

### 4 LED Color Temp

27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

### 5 LED Dimming

D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

### 6 Voltage Options

120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

WH: White Acrylic  
 FX: Faux Alabaster Acrylic

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser